

ARSET

Applied Remote Sensing Training http://arset.gsfc.nasa.gov

Creating and Using Normalized Difference Vegetation Index (NDVI) from Satellite Imagery

Instructors: Cindy Schmidt and Amber McCullum

Week 4

Homework and Certificates


- Homework
 - Hands-on exercise each week
 - Answers must be submitted via Google Form
- Certificate of Completion:
 - Attend all 4 webinars
 - Complete all 4 homework assignments by the deadline (access from ARSET website)
 - Week 4 Deadline: Wednesday March 16th
 - You will receive certificates in approximately 2 months from: <u>marines.martins@ssaihq.com</u>



Accessing Course Materials

• http://arset.gsfc.nasa.gov/ecoforecasting/webinars/advanced-webinar-creating-and-using-normalized-difference-vegetation-index






Course materials are provided here using each specified link and will be active after each week

Course Outline

Week 1


Overview of NDVI and QGIS



Week 3


MODIS NDVI Time Series





Week 2

NDVI with Landsat





Week 4

MODIS NDVI Anomaly Mapping

Week 3 Review


- MODIS data characteristics
- Where to Obtain MODIS Products
- GLAM Websites:
 - Global 16-day 250 m NDVI time series database
 - GIMMS MODIS monitoring system





Week 4 Agenda

- Overview of additional Landsat indices
- Overview of MODIS scaling factor
- Overview of MODIS NDVI Mapping
- Exercise: Creating a MODIS NDVI Anomaly Map
- Q&A
- Survey




MRT Web User Interface



Landsat Spectral Indices

- Enhanced Vegetation Index (EVI- reviewed last week)
- Soil Adjusted Vegetation Index (SAVI)
- Modified Soil Adjusted Vegetation Index (MSAVI)
- Normalized Difference Moisture Index (NDMI)
- Normalized Burn Ratio (NBR) and Difference Normalized Burn Ratio (dNBR)




Burn Severity Map from New Mexico Silver Fire: Image Credit: USFS

Soil Adjusted Vegetation Index

- Minimizes soil brightness influences
- Useful in areas with greater soil cover
 - Contains a soil brightness correction factor (L)
 - 0.5 typically used
 - Lower for areas with greater canopy cover
 - Higher for areas with less canopy cover

$$SAVI = \left(\frac{(NIR - R)}{(NIR + R + L)}\right) \times (1 + L)$$




SAVI: Image Credit: Grind GIS

Soil Adjusted Vegetation Index

- Remember: Landsat Bands
 - Landsat 4-7
 - NIR = Band 4
 - R = Band 3
 - Landsat 8
 - NIR = Band 5
 - R = Band 4


Example of SAVI using the California Landsat scene from week 2 exercise



Modified Soil Adjusted Vegetation Index

$$MSAVI = \frac{\left(2 \times NIR + 1 - \sqrt{\left(2 \times NIR + 1\right)^2 - 8 \times \left(NIR - R\right)}\right)}{2}$$


- Inductive L function
 - Do not need to specify soil correction factor
- Designed to maximize reduction of soil effects on the vegetation signal



Normalized Difference Moisture Index (NDMI)

- Measure of vegetation moisture
- Frequently used in drought monitoring
 - Detects more subtle changes in vegetation moisture
- Used in wildfire hazard potential

$$NDMI = \frac{\left(NIR - SWIR\right)}{NIR + SWIR}$$



Example of NDMI. Image Credit: Wang and Qu, 2007

Normalized Difference Moisture Index (NDMI)

- Remember: Landsat Bands
 - Landsat 4-7
 - NIR = Band 4
 - SWIR = Band 5
 - Landsat 8
 - NIR = Band 5
 - SWIR = Band 6

$$NDMI = \frac{\left(NIR - SWIR\right)}{NIR + SWIR}$$

Example of California from week 2 exercise

NDMI using the Landsat scene


Normalized Burn Ratio

- Used to identify burned areas
- Compare pre and post-burn to identify burn extent and severity
- Use Band 7 for SWIR in Landsat images

Example of NBR using the California Landsat scene from week 2 exercise:

Rim Fire


$$NBR = \frac{\left(NIR - SWIR\right)}{NIR + SWIR}$$



Normalized Burn Ratio Difference Map

- Need at least 2 images:
 - One pre-burn
 - One post-burn
- 1. Create NBR for each image
- 2. Subtract post-fire image from prefire image
- 3. Evaluate differenced map

$$dNBR = NBR_{prefire} - NBR_{postfire}$$



Example of dNBR. Image Credit: Irene Nester



Surface Reflectance Products

- Standard Landsat 8 imagery provide calibrated scaled digital numbers: no corrections
- Surface Reflectance products apply atmospheric correction for:
 - Water vapor
 - Ozone and aerosol optical thickness
 - Geopotenital height
 - Digital elevation
 - Masks for clouds and cloud shadows




Landsat 8 Surface Reflectance Product: Composite Moasic for Australia: Image Credit USGS

Surface Reflectance Products

- Surface Reflectance products generated from the Landsat Ecosystem Disturbance Adaptive Processing System (LEDAPS)
 - Originally developed by NASA
- Available from EarthExplorer:
 - http://earthexplorer.usgs.gov/

Landsat 4-7 and 8 Surface Reflectance Products Available from EarthExplorer



Surface Reflectance Products: Specifications


- 30 meter spatial resolution
- Universal Transverse Mercator (UTM) or Polar Steregoraphic (PS) grid
- Download as GeoTIFF
- Original scene name with "_sr_" followed by band designation
- More information: http://landsat.usgs.gov/CDR_LSR.php




Example of the unprocessed Landsat image (left) and the LEDAPS processed Landsat image (right)

Surface Reflectance Products: Caveats

- Products considered provisional
- Landsat 7 images not gap-filled
- Usefulness of surface reflectance products reduced in:
 - Hyper-arid or snow-covered regions
 - Low sun angle conditions
 - Coastal regions
 - Areas with extensive clouds
- Panchromatic band (ETM+ Band 8) not processed
- Specific date ranges for Landsat 4,5,7





Reminder: NDVI Anomalies

- Departure of NDVI from the long-term average, normalized by long-term variability
- Generated by subtracting the long-term mean from the current value for that month of the year for each grid cell.
- Indicates if vegetation greenness at a particular location is typical for that period or if the vegetation is more or less green



NDVI Anomalies in the southwestern United States. Image Credit: NASA/Goddard Space Flight Center Scientific Visualization Studio.

Reminder: MODIS Scaling Factor

- Before calculating NDVI anomalies we must multiple by the MODIS scaling factor
- Data Storage: less storage needed if pixel values do not contain decimals.
 - Thus, before we conduct processing to the image, a scaling factor is used:

MODIS SCALING FACTOR: 0.0001

Must multiple entire image by 0.0001





Image Credit: NASA Earth Observatory



Contacts

- ARSET Land Management and Wildfire Contacts
 - Cynthia Schmidt: Cynthia.L.Schmidt@nasa.gov
 - Amber McCullum: AmberJean.Mccullum@nasa.gov
- General ARSET Inquiries
 - Ana Prados: aprados@umbc.edu
- ARSET Website:
 - http://arset.gsfc.nasa.gov/

Survey

- Thank you for your participation in our webinar series. We would appreciate it if you could take a few minutes to complete our end-ofcourse survey.
- The link will be provided in the chat box.



ARSET

Applied Remote Sensing Training http://arset.gsfc.nasa.gov

Thank You

Remember: Complete homework assignments!

www.nasa.gov

